

Youth Dwellings in Copenhagen

Inward Opening Fire-Rated Window

ALUFLAM is proud to present a new window system with an exceptionally low profile that opens inwards.


The profile height of 54 mm ensures not only lightness and aesthetics but also full coherence with all other products of the A+ family. This system complies with the EI60 classification for both sides, internal and external.




Inward opening fire-rated window from the A+ family

- **Fire resistance** – EI60 class
- **Visual effect** – narrow window frame with 54 mm sightline ensures full visual and system compatibility with all other A+ family products
- **Universal installation** – the possibility of installation as a single window in the wall construction and as an element of the facade system
- **Numerous frame depths** – wide palette of frame profiles with different depths and types of sightline: straight and bevel
- **Numerous colours and finishes** – aluminium profiles available in diverse RAL colours and anodised

Window



Facade window (example with facade AW50)



Fire resistance	EI60 / EW60 / E60 (internal & external side)
Functionality	Turn & Tilt
Material	Aluminium RAL/anodized
Maximal size	1244 x 1104 mm
Minimal size	700 x 700 mm
Sightline	54 mm
Available frame depths	85 / 95 / 149 / 159 / 174 mm

ALUFLAM A/S
Langebjergvænget 13
4000 Roskilde
DENMARK

Tel. +45 46 75 06 11
Fax +45 46 75 08 11
E-mail: info@aluflam.dk
VAT Reg No 20675136

ALUFLAM[®]
GROUP